

The VersaLink C7000 Color Printer is built on Xerox<sup>®</sup> ConnectKey<sup>®</sup> Technology. For more information, go to www.connectkey.com.



System Specifications	VersaLink C7000N	VersaLink C7000DN
<b>One-Sided Speed</b> 8.5 x 11 in. / A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm 11 x 17 in. / A3 / 297 x 420 mm	Up to 35 ppm (pages per minute) long edge feed (LEF) Up to 22 ppm Up to 19 ppm	
<b>Two-Sided Speed</b> 8.5 x 11 in. / A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm 11 x 17 in. / A3 / 297 x 420 mm	NA	Up to 35 ppm (pages per minute) LEF Up to 14 ppm Up to 13 ppm
Monthly Duty Cycle <sup>1</sup>	Up to 153,000 pages / month <sup>1</sup>	
Recommended Average Monthly Print Volume <sup>2</sup>	Up to 10,000 pages	
Hard Drive	320 GB HDD (Optional)	
Processor	1.05 GHz Dual-Core	
Memory	2 GB	
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n/g/b/a and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair	
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform <sup>®</sup> , Xerox App Gallery, Xerox <sup>®</sup> Standard Accounting, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support (accessed from the user interface and print driver)	
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian	

Device Specifications				
Electrical Requirements				
North America	Voltage: 110-127V -10 % / +6 % Frequency: 50/60 Hz +/-3 % , 12A			
Europe and Other Geographies	Voltage: 220-240V +/- 10 % Frequency: 50 Hz +/-3 % , 8A			
Power Consumption				
Printing <sup>3</sup>	For 110V: 1.6 kWh For 220V: 1.6 kWh			
Standby Mode <sup>3</sup>	110V: 94 Watts or less 220V: 94 Watts or less			
Sleep Mode <sup>3</sup>	110V: 1.0 watts or less 220V: 1.4 watts or less			
Operating Environment	•			
Required Temperature Range (Storage)	32° to 95° F (0° to 35° C)			
Required Temperature Range (Operating)	50 to 90° F (10 to 32° C)			
Required Relative Humidity	10% to 85%			
Sound Power Levels	Printing: 6.75 B(A) or less Standby: 4.10 B(A) or less <b>Full System (including finisher)</b> Printing: 7.52 B(A) Standby: 4.10 B(A)			
Sound Pressure Levels	Printing: 52.5 dB(A) Standby: 26.0 dB(A) Full System (including finisher) Printing: 60.0 dB(A) Standby: 26.0 dB(A)			
Boot Time (from Off to UI Ready)	As fast as 98 seconds			
Warm-up Time (from Sleep to UI Ready)	As fast as 12 seconds			
Dimensions and Weight (Unpackaged)	Width	Depth	Height	Weight
Base Unit	23.23 in. / 590 mm	26.41 in. / 670.8 mm	25.08 in. / 637 mm	119.71 lb. / 54.3 kg
Base Unit with Single Tray with Stand Module	24.24 in. / 615.7 mm	26.41 in. / 670.8 mm	44.04 in. / 1118.6 mm	171.08 lb. / 77.6 kg
Base Unit with Three Tray Module	24.24 in. / 615.7 mm	26.41 in. / 670.8 mm	44.04 in. / 1118.6 mm	178.75 lb. / 81.8 kg
Base Unit with Three Tray Module and Integrated Office Finisher	24.24 in. / 615.7 mm	26.41 in. / 670.8 mm	44.04 in. / 1118.6 mm	215.17 lb. / 97.6 kg
Certifications				·
To view the latest list of certificatio	ns, go to www.xerox.com/	OfficeCertifications.		

Print		
First-print-out Time	As fast as 7.6 seconds Color	
	As fast as 5.1 seconds Black	
Print Resolution	Up to 1200 x 2400 dpi	
Page Description Languages	Adobe <sup>®</sup> PostScript <sup>®</sup> 3 <sup>™</sup> PCL <sup>®</sup> 5e, 6 PDF XPS TIFF JPEG HP-GL	
Maximum Print Area	4 mm from lead edge of paper, 2 mm from Side and Trail edges of paper	
Print Features	Application Defaults         Banner Pages Enable / Disable         Bi-directional Real-time Status         Booklet Layout         Color Adjustments (lightness, contrast, saturation, color balance)         Color Correction         Draft Mode         Finishing (requires finishing)         Fit to new paper size         Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages)         Job Monitoring (Client or Local User Interface)         N-up Page Layout (up to 16 pages per sheet)         Paper Selection by Attribute         Personal Print         Print Around Enable / Disable         Print from USB         Run Black         Sample Set         Saved Job         Scaling         Secure Print         Skip Blank Pages         Special Pages (exception page programming: covers, inserts, exceptions pages)         Store and Recall Driver Settings         Stored Jobs Deletion         Two-sided Printing (as default – DN configuration)         Watermark (predefined and custom)         Xerox <sup>®</sup> Earth Smart Driver Settings	
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A	
Operating Systems	Windows® 7, 8, 8.1, 10         Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016         macOS® 10.11, 10.12, 10.13         Citrix®         Redhat® Enterprise Linux®         Fedora Core         IBM® AIX®         HP-UX®         Oracle® Solaris         SUSE®         SAP®         Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com.	
Fonts	PostScript fonts: 136 PCL fonts: 83	

Xerox <sup>®</sup> Mobile Express Driver <sup>®</sup>	Makes it easy for mobile users to find, use and manage Xerox <sup>®</sup> and non-Xerox <sup>®</sup> devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.	
Xerox <sup>®</sup> Global Print Driver <sup>®</sup>	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox <sup>®</sup> and non-Xerox <sup>®</sup> devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Xerox <sup>®</sup> Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox <sup>®</sup> Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office <sup>®</sup> , Ysoft <sup>®</sup> SafeQ <sup>®</sup> , Pharos <sup>®</sup> and others.	
Mobile Solutions and Mobile Devi	ce Apps	
Apple <sup>®</sup> AirPrint <sup>®</sup>	Print email, photos and important office documents directly from an Apple iPhone <sup>®</sup> or iPad <sup>®</sup> with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.	
Google Cloud Print™	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device.	
@PrintByXerox	@PrintByXerox is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android <sup>™</sup> , Google <sup>®</sup> Chromebook <sup>™</sup> and more) to a Xerox <sup>®</sup> printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel.	
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox <sup>®</sup> Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play <sup>™</sup> store.	
Xerox <sup>®</sup> Print Management and Mobility Suite, Xerox <sup>®</sup> Print Management and Mobility Service	Xerox <sup>®</sup> Print Management and Mobility Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version and with a cloud based-version of this solution.	
Software Solutions		
Xerox® ConnectKey® Apps (Found at the Xerox® App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the device.	

Security	
Security Features	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of external program falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS/SSL
Accounting	
Xerox <sup>®</sup> Standard Accounting / Ne	twork Accounting (Standard)
Tracking	Print usage
Accounting	Xerox <sup>®</sup> Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General accounts Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 accounting records (transactions)
Features	Administrator can manage the feature via the Embedded Web Server.
Accounting Options – Network Ac	counting (Allows central server to manage all accounting)
	<ul> <li>Enhanced network accounting with up to the minute data on how the system is being used</li> <li>Comprehensive management and enterprise scale tracking and reporting of device print usage</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com</li> <li>Security enhancements include simultaneous support for HTTP/HTTPS protocols</li> <li>Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third party Networking Account</li> </ul>
Paper Handling	
Bypass Tray	
Capacity <sup>4</sup>	100 sheets
Sizes	Custom sizes: 3.5 x 3.87 in. to 11.69 x 17 in. / 88.9 x 98.4 mm to 297 x 431.8 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 80 lb. cover / 60 to 216 gsm 16 lb. bond to 60 lb. cover / 60 to 169 gsm

Types	Bond Plain Paper Cardstock Custom Envelopes Hole Punched Labels Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Pre-Printed Recycled
Tray 1	
Capacity <sup>4</sup>	520 sheets
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 95 lb. cover / 60 to 256 gsm 16 lb. bond to 60 lb. cover / 60 to 169 gsm
Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Reload Recycled
Single Tray Module (Opt	ional)
Capacity <sup>4</sup>	520 sheets
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 95 lb. cover / 60 to 256 gsm 16 lb. bond to 60 lb. cover / 60 to 169 gsm
Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled

Single Tray Module wit	h Stand (Optional)	
Capacity <sup>4</sup>	520 sheets	
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm	
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 95 lb. cover / 60 to 256 gsm 16 lb. bond to 60 lb. cover / 60 to 169 gsm	
Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled	
Three Tray Module (Op	tional)	
Capacity <sup>4</sup>	Tray 2: 520 sheets Tray 3: 520 sheets Tray 4: 520 sheets	
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm	
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 95 lb. cover / 60 to 256 gsm 16 lb. bond to 60 lb. cover / 60 to 169 gsm	
Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Recycled	
Envelope Tray – Replaces Tray 1 (Optional)		
Capacity <sup>4</sup>	Up to 60 envelopes	
Sizes	#10 commercial, Monarch, DL, C5 Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148 mm to 162 x 241 mm	
Weights	20 lb. bond to 25 lb. bond / 75 to 90 gsm	

Total Capacity		
Base Unit Capacity <sup>4</sup>	620 sheets	
Single Tray Module Capacity <sup>4</sup>	1,140 sheets	
Single Tray Module with Stand Capacity <sup>3</sup>	1,140 sheets	
Three Tray Module Capacity <sup>4</sup>	2,180 sheets	
Finishing		
Output Trays		
Center Output Catch Trays	500 sheets; tray offsets	
Integrated Office Finisher (Option	nal)	
Stacking Tray	500 sheets of 20 lb. bond / 80 gsm – 8.5 x 11 in. / A4 or 250 sheets of 20 lb. bond / 80 gsm – 11 x 17 in. / A3	
Sizes	3.5 x 3.9 in. to 11.7 x 17 in. / 89 x 98 mm to 297 x 432 mm	
Weights	16 lb. bond to 80 lb. cover / 60 to 220 gsm	
Stapling	Single Auto stapling: 50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers)	
Device Management		
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour® / AirPrint™ Most protocols not in use can be disabled	
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS	
Xerox <sup>®</sup> CentreWare <sup>®</sup> Web		
	<ul> <li>A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>Works with any SNMP-managed printer from any manufacturer</li> <li>Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>	
Xerox <sup>®</sup> Embedded Web Server – I	ntegrated Device Web Page	
Device Status	<ul> <li>Tray status/contents</li> <li>Consumables status</li> <li>Billing/Usage</li> <li>Quick Links</li> <li>Online Support</li> </ul>	
Print Queue Viewing	Job print queue management—view and delete	
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG)	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device	
Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™	

Remote Services		
Xerox <sup>®</sup> Meter Assistant <sup>®</sup> Service	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.	
Xerox <sup>®</sup> Supplies Assistant <sup>®</sup> Service	Automatically orders supplies for Xerox <sup>®</sup> output devices based on actual usage, eliminating the need to manually manage supplies inventory.	
MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.	
What's In The Box		
	<ul> <li>VersaLink C7000 Color Printer</li> <li>Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow: 3,300 print capacity<sup>5</sup>, Black: 5,300 print capacity<sup>5</sup></li> <li>Imaging Drum – One of each (Cyan, Magenta, Yellow, Black: 82,200 print capacity)<sup>7</sup></li> <li>Quick Use Guide</li> <li>Quick Install Guide</li> <li>Software and Documentation CD (with Drivers, User Manual, System Admin. Guide and Warranty Statement)</li> <li>Power Cord</li> </ul>	

Supplies and Accessories	Quantity	Part Number	
Supplies			
Standard Capacity Print Cartridges	Cyan: 3,300 standard pages <sup>5</sup> Magenta: 3,300 standard pages <sup>5</sup> Yellow: 3,300 standard pages <sup>5</sup> Black: 5,300 standard pages <sup>5</sup>	106R03764 106R03763 106R03762 106R03761	
High Capacity Print Cartridges	Cyan: 10,100 standard pages <sup>5</sup> Magenta: 10,100 standard pages <sup>5</sup> Yellow: 10,100 standard pages <sup>5</sup> Black: 10,700 standard pages <sup>5</sup>	106R03760 106R03759 106R03758 106R03757	
Worldwide Metered Print Cartridge	Cyan: 10,100 standard pages <sup>6</sup> Magenta: 10,100 standard pages <sup>6</sup> Yellow: 10,100 standard pages <sup>6</sup> Black: 10,700 standard pages <sup>6</sup>	106R03756 106R03755 106R03754 106R03753	
CMYK Drum Cartridge	82,200 standard pages <sup>7</sup>	113R00782	
Waste Toner Bottle	21,200	115R00129	
Fuser	120V Fuser 220V Fuser	115R00137 115R00138	
Staple Refills for Finishers (3 refills per container)	15,000 staples (5,000 each refill)	008R12941	
Staple Cartridge for Finishers (1 cartridge per container)	5,000 staples (5,000 each cartridge)	008R12964	
Accessories / Options			
Single Tray Module (does not include stand)		097504910	
Single Tray with Stand Module		097504907	
Three Tray Module		097504908	
Envelope Tray (This replaces Tray 1		497K17720	
Integrated Office Finisher		097504911	
HDD (320 GB hard drive) (Optional)		497K17740	
Wireless Network Adapter Kit		497K16750	
Internal Card Reader / RFID Kit		497K18120 (Western Hemisphere) 497K18140 (Eastern Hemisphere)	

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
 <sup>2</sup> Expected regular monthly throughput.
 <sup>3</sup> Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.
 <sup>4</sup> Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.
 <sup>5</sup> Average standard pages. Declared Viled in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.
 <sup>6</sup> Assumptions: Toner cartridge yield is based on 5% area coverage on 8.5 x 11 in. / A4 LEF. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, run mode, application types, monthly print volumes and image quality set-points.
 <sup>7</sup> Assumptions: Concerced will vary will vary due to media size/orientation and machine speed. For more information visit: http://www.office.verox.com/latest/SUPGL-01.pdf.

<sup>7</sup> Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: http://www.office.xerox.com/latest/SUPGL-01.pdf.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/about-xerox/recycling.

For more information, visit us at www.xerox.com/office

Configurations vary by geography.



©2018 Xerox Corporation. All rights reserved. Xerox®, Xerox and Design®, CentreWare®, ConnectKey® Global Print Driver®, Mobile Express Driver®, SuppliesAssistant® and VersaLink® are trademarks of Xerox Corporation in the United States and/or other countries. The information in this brochure is subject to change without notice. Updated 3/18 VCVSS-01UC